NSN 4720-01-358-8979

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-358-8979

view Offilite at https://aerobasegroup.com/hsh/+/20-01-550-05/5
Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.362 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 275.0 degrees fahrenheit single response
Outside Diameter:
0.570 inches
Minimum Inside Bending Radius:
0.750 inches
Exterior Color:
Black
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
800.0 pounds per square inch
Maximum Operating Pressure:
200.0 pounds per square inch
Thread Size:
0.563 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
300.0 pounds per square inch
Outer Covering Environmental Protection:
Fire resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
12.280 inches
Supplementary Features:
This item has been reviewed for asbestos material; the current approved soucrs, 78570 have indicated their part number contained asbestos
prior to 1984, they continue to manufacture the same part nuber without asbestos material after 1984

Unjf 1st end

Thread Series Designator:

NSN 4720-01-358-8979

Nonmetallic Hose Assembly - Page 2 of 2



_				
c	hο	JIF.		ife:
J	116		_	HG.

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0