## NSN 4720-01-359-0601

**Cross Sectional Shape:** 

Round

Thread Class: 3b 1st end

12.310 inches

Thread Direction: Right-hand 1st end

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-359-0601

Inside Diameter:
0.355 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 275.0 degrees fahrenheit single response
Outside Diameter:
0.575 inches
Minimum Inside Bending Radius:
0.750 inches
Exterior Color:
Black or blue
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability and nuts drilled for lockwire
Burst Test Pressure:
900.0 pounds per square inch
Layer Composition And Location:
Outer layer braided polyamide cord
Maximum Operating Pressure:
300.0 pounds per square inch
Thread Size:
0.562 inches 2nd end
Seat Angle:
37.0 degrees 2nd end
Hydrostatic Test Pressure:
600.0 pounds per square inch
Flow Angle:
90.0 degrees 2nd end
Inside Surface Condition:
Convoluted
Measuring Method And Length:

## NSN 4720-01-359-0601

Nonmetallic Hose Assembly - Page 2 of 2



Special	Features:
---------	-----------

Crimped fittings

**Thread Series Designator:** 

Unjf 1st end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0