

View Online at <https://aerobasegroup.com/nsn/4720-01-359-0603>

**Cross Sectional Shape:**

Round

**Thread Class:**

3b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.510 inches

**Temperature Rating:**

-65.0 degrees fahrenheit single response and 275.0 degrees fahrenheit single response

**Outside Diameter:**

0.760 inches

**Minimum Inside Bending Radius:**

1.000 inches

**Exterior Color:**

Black or blue

**Connection Style:**

Swivel nut flare 2nd end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Threaded internal tube 1st end

**Features Provided:**

Electrostatic discharge capability and nuts drilled for lockwire

**Burst Test Pressure:**

750.0 pounds per square inch

**Layer Composition And Location:**

Outer layer braided polyamide cord

**Maximum Operating Pressure:**

250.0 pounds per square inch

**Thread Size:**

0.750 inches 2nd end

**Seat Angle:**

37.0 degrees 2nd end

**Hydrostatic Test Pressure:**

500.0 pounds per square inch

**Flow Angle:**

90.0 degrees 2nd end

**Vacuum In Torr:**

50.8

**Inside Surface Condition:**

Convuluted

**Measuring Method And Length:**

6.750 inches

**Special Features:**

Crimped fittings

**Thread Series Designator:**

Unjf 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0