Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-359-2395

Cross Sectional S	hape:
Round	
Thread Class:	
2b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.250 inches	
Tempurature Ratin	ng:
-40.0 degrees fahre	nheit single response and 200.0 degrees fahrenheit single response
Outside Diameter:	
0.590 inches	
Minimum Inside B	ending Radius:
4.000 inches	
Connection Style:	
Swivel nut, invertee	d flare 2nd end
End Connection D	esign:
Elbow 2nd end	
Connection Type:	
Threaded external	ube 2nd end
Thready Qty Per In	nch (tpi):
24 2nd end	
Burst Test Pressu	re:
20000.0 pounds pe	r square inch
Maximum Operati	ng Pressure:
5000.0 pounds per	square inch
Thread Size:	
0.438 inches 1st en	d
Seat Angle:	
37.0 degrees 2nd e	nd
Flow Angle:	
90.0 degrees 1st er	nd
Inside Surface Co	ndition:
Smooth	
Measuring Method	I And Length:
5.780 inches	
Special Features:	
Do not dupe to othe	er nsn's - crimped end is unique to the crimping machine of the manufacturer; first end elbow, imperial p/n hu04-04mf90t;
	imperial p/n hu04-04mf45t
Media For Which I	
Fuel/oil, hydrocarb	
Thread Series Des	
Uns 2nd end	

NSN 4720-01-359-2395

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0

