## NSN 4720-01-359-2404

**Cross Sectional Shape:** 

Round

Thread Class: 3b 1st end

Thread Direction: Right-hand 1st end

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-359-2404

Inside Diameter:
0.780 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 2754.0 degrees fahrenheit single response
Outside Diameter:
1.070 inches
Minimum Inside Bending Radius:
2.000 inches
Exterior Color:
Black
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
End Fitting Component And Material:
Complete fitting aluminum alloy all ends
Connection Type:
Threaded internal tube 1st end
Features Provided:
Nuts drilled for lockwire
Nuts drilled for lockwire  Thready Qty Per Inch (tpi):
Thready Qty Per Inch (tpi):
Thready Qty Per Inch (tpi): 12 1st end
Thready Qty Per Inch (tpi):  12 1st end  Second End Relationship With First End:
Thready Qty Per Inch (tpi):  12 1st end  Second End Relationship With First End: Identical
Thready Qty Per Inch (tpi):  12 1st end  Second End Relationship With First End:  Identical  Burst Test Pressure:
Thready Qty Per Inch (tpi):  12 1st end  Second End Relationship With First End:  Identical  Burst Test Pressure:  600.0 pounds per square inch
Thready Qty Per Inch (tpi):  12 1st end  Second End Relationship With First End: Identical  Burst Test Pressure:  600.0 pounds per square inch  First End Swivel Action Capability:
Thready Qty Per Inch (tpi):  12 1st end  Second End Relationship With First End:  Identical  Burst Test Pressure:  600.0 pounds per square inch  First End Swivel Action Capability:  Not included
Thready Qty Per Inch (tpi):  12 1st end  Second End Relationship With First End: Identical  Burst Test Pressure:  600.0 pounds per square inch  First End Swivel Action Capability:  Not included  Layer Composition And Location:
Thready Qty Per Inch (tpi):  12 1st end  Second End Relationship With First End: Identical  Burst Test Pressure:  600.0 pounds per square inch  First End Swivel Action Capability: Not included  Layer Composition And Location:  Outer layer braided textile yarn err-100
Thready Qty Per Inch (tpi):  12 1st end  Second End Relationship With First End: Identical  Burst Test Pressure: 600.0 pounds per square inch  First End Swivel Action Capability: Not included  Layer Composition And Location: Outer layer braided textile yarn err-100  Maximum Operating Pressure:
Thready Qty Per Inch (tpi):  12 1st end  Second End Relationship With First End:  Identical  Burst Test Pressure:  600.0 pounds per square inch  First End Swivel Action Capability:  Not included  Layer Composition And Location:  Outer layer braided textile yarn err-100  Maximum Operating Pressure:  200.0 pounds per square inch
Thready Qty Per Inch (tpi):  12 1st end  Second End Relationship With First End: Identical  Burst Test Pressure: 600.0 pounds per square inch  First End Swivel Action Capability: Not included  Layer Composition And Location: Outer layer braided textile yarn err-100  Maximum Operating Pressure: 200.0 pounds per square inch  Thread Size:

## NSN 4720-01-359-2404

Nonmetallic Hose Assembly - Page 2 of 2



Hydrostatic Test Pressure:
400.0 pounds per square inch
Inside Surface Condition:
Convoluted
Measuring Method And Length:
12.000 inches
Special Features:
Nuts drilled for lockwire, 2 holes .070 dia.Each end
Thread Series Designator:
Unj 1st end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A542a0