NSN 4720-01-359-2405

Cross Sectional Shape:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-359-2405

Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.370 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 275.0 degrees fahrenheit single response
Outside Diameter:
0.560 inches
Minimum Inside Bending Radius:
0.750 inches
Exterior Color:
Black
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Nuts drilled for lockwire
Burst Test Pressure:
900.0 pounds per square inch
Layer Composition And Location:
Outer layer braided textile yarn
Maximum Operating Pressure:
300.0 pounds per square inch
Thread Size:
0.5625 inches 1st end
Seat Angle:
45.0 degrees 1st end
Hydrostatic Test Pressure:
600.0 pounds per square inch
Inside Surface Condition:
Convoluted
Measuring Method And Length:
11.500 inches working
Special Features:
Nuts drilled for lockwires both ends; .047 dia.

NSN 4720-01-359-2405

Nonmetallic Hose Assembly - Page 2 of 2



Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0