NSN 4720-01-359-2406

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-359-2406 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.370 inches **Tempurature Rating:** -65.0 degrees fahrenheit and 275.0 degrees fahrenheit single response **Outside Diameter:** 0.560 inches **Minimum Inside Bending Radius:** 0.750 inches **Connection Style:** Swivel nut flare 2nd end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Features Provided:** Nuts drilled for lockwire **Burst Test Pressure:** 900.0 pounds per square inch **Layer Composition And Location:** 1st layer braided polyester cord and outer layer molded rubber, synthetic **Maximum Operating Pressure:** 300.0 pounds per square inch **Thread Size:** 0.562 inches 2nd end Seat Angle: 30.0 degrees 2nd end **Hydrostatic Test Pressure:** 600.0 pounds per square inch Flow Angle: 90.0 degrees 2nd end **Inside Surface Condition:** Smooth **Measuring Method And Length:**

17.000 inches working

Thread Series Designator:

Unjf 1st end

NSN 4720-01-359-2406

Nonmetallic Hose Assembly - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0