## NSN 4720-01-360-2376

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-360-2376 **Cross Sectional Shape:** Round **Inside Diameter:** 1.500 inches **Tempurature Rating:** -32.0 degrees celsius and 52.0 degrees celsius single response **Quick Disconnect Size:** 1.500 inches 2nd end **End Application:** 4930-01-274-0021 **Connection Style:** Cam or lever (external) 2nd end **End Connection Design:** Straight 2nd end **Connection Type:** Internal quick disconnect 1st end **Features Provided:** Reusable end fittings **Burst Test Pressure:** 500.0 pounds per square inch **Layer Composition And Location:** 1st layer rubber impregnated braided cotton cord and 2nd layer rubber impregnated braided cotton cord and outer layer molded rubber, synthetic **Maximum Operating Pressure:** 150.0 pounds per square inch **Hydrostatic Test Pressure:** 300.0 pounds per square inch **Outer Covering Environmental Protection:** Fuel resistant and oil resistant and mildew resistant and ozone resistant **Inside Surface Condition:** Smooth **Measuring Method And Length:** 38.500 inches excluding end fittings **Specification Data:** 81349-mil-h-370 government specification Shelf Life: N/a **Unit Of Measure:** 

No Fiig:

A542a0

**Demilitarization:** 

## NSN 4720-01-360-2376

Nonmetallic Hose Assembly - Page 2 of 2



Mil-std (military Standard):

Mil-prf-370 spec.