Nonmetallic Hose Assembly - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/4720-01-360-2376

Cross Sectional Shape:

Round

Inside Diameter:

1.500 inches

Tempurature Rating:

-32.0 degrees celsius and 52.0 degrees celsius single response

Quick Disconnect Size:

1.500 inches 2nd end

End Application:

4930-01-274-0021

Connection Style:

Cam or lever (external) 2nd end

End Connection Design:

Straight 2nd end

Connection Type:

Internal quick disconnect 1st end

Features Provided:

Reusable end fittings

Burst Test Pressure:

500.0 pounds per square inch

Layer Composition And Location:

1st layer rubber impregnated braided cotton cord and 2nd layer rubber impregnated braided cotton cord and outer layer molded rubber, synthetic

Maximum Operating Pressure:

150.0 pounds per square inch

Hydrostatic Test Pressure:

300.0 pounds per square inch

Outer Covering Environmental Protection:

Fuel resistant and oil resistant and mildew resistant and ozone resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

38.500 inches excluding end fittings

Specification Data:

81349-mil-h-370 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0



Mil-std (military Standard):

Mil-prf-370 spec.