## NSN 4720-01-360-4360

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-360-4360

**Cross Sectional Shape:** 

Round

**Inside Diameter:** 

2.000 inches

**Tempurature Rating:** 

-32.0 degrees celsius single response and 52.0 degrees celsius single response

### First End Fitting Specification/std Data:

Mil-c-27487, type 6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### Second End Fitting Specification/std Data:

Mil-c-27487, type 2 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Quick Disconnect Size:**

2.000 inches 2nd end

**End Application:** 

4930-01-027-4002

**Connection Style:** 

Cam or lever (external) 2nd end

**End Connection Design:** 

Straight 2nd end

#### **End Fitting Component And Material:**

Complete fitting aluminum alloy all ends

**Connection Type:** 

Internal quick disconnect 1st end

**Features Provided:** 

Reusable end fittings

Second End Relationship With First End:

Not identical

**Burst Test Pressure:** 

400.0 pounds per square inch

First End Swivel Action Capability:

Not included

**Layer Composition And Location:** 

1st layer rubber impregnated braided cotton cord err-100

**Maximum Operating Pressure:** 

125.0 pounds per square inch

**Hydrostatic Test Pressure:** 

250.0 pounds per square inch

#### **Outer Covering Environmental Protection:**

Fuel resistant and oil resistant and mildew resistant and ozone resistant

**Inside Surface Condition:** 

Smooth

Measuring Method And Length:

# NSN 4720-01-360-4360

Nonmetallic Hose Assembly - Page 2 of 2



Second End Swivel Action Capability:
Not included
Specification Data:
81349-mil-h-370 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A542a0

Mil-std (military Standard):

Mil-c-27487 spec.