Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-361-5113

# Cross Sectional Shape:

Round

**Thread Class:** 

3b 1st end

# Thread Direction:

Right-hand 1st end

## Inside Diameter:

0.375 inches

#### **Tempurature Rating:**

-70.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

### **Outside Diameter:**

0.650 inches

### Minimum Inside Bending Radius:

2.000 inches

#### Exterior Color:

Black

#### **Connection Style:**

Swivel nut flare 1st end

#### **End Connection Design:**

Straight 1st end

# Connection Type:

Threaded internal tube 1st end

### **Features Provided:**

Perforated outer cover

### **Burst Test Pressure:**

9000.0 pounds per square inch

### Layer Composition And Location:

1st layer braided fiber and 2nd layer braided fiber and outer layer polyester

### Maximum Operating Pressure:

2250.0 pounds per square inch

#### Thread Size:

0.750 inches 1st end

#### Seat Angle:

37.0 degrees 1st end

### Inside Surface Condition:

Smooth

### Measuring Method And Length:

1110.000 inches

#### **Special Features:**

Fittings are permanent; cover is thermoplastic 90 a durometer hardness with hose support grip supplied by parker-hannifin corp.

# **Thread Series Designator:**

Unf 1st end

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A542a0

