## NSN 4720-01-363-2235

Nonmetallic Hose Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-01-363-2235

Round Tempurature Rating: -40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 20000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, synthetic Maximum Operating Pressure: 5000.0 pounds per square inch Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure:
-40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response  Connection Style:  Swivel nut flare 1st end  End Connection Design:  Straight 1st end  Connection Type:  Threaded internal tube 1st end  Burst Test Pressure:  20000.0 pounds per square inch  Layer Composition And Location:  1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, synthetic  Maximum Operating Pressure:  5000.0 pounds per square inch  Seat Angle:  37.0 degrees 1st end
Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 20000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, synthetic Maximum Operating Pressure: 5000.0 pounds per square inch Seat Angle: 37.0 degrees 1st end
Swivel nut flare 1st end  End Connection Design: Straight 1st end  Connection Type: Threaded internal tube 1st end  Burst Test Pressure: 20000.0 pounds per square inch  Layer Composition And Location: 1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, synthetic  Maximum Operating Pressure: 5000.0 pounds per square inch  Seat Angle: 37.0 degrees 1st end
End Connection Design:  Straight 1st end  Connection Type:  Threaded internal tube 1st end  Burst Test Pressure:  20000.0 pounds per square inch  Layer Composition And Location:  1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, synthetic  Maximum Operating Pressure:  5000.0 pounds per square inch  Seat Angle:  37.0 degrees 1st end
Straight 1st end  Connection Type: Threaded internal tube 1st end  Burst Test Pressure: 20000.0 pounds per square inch  Layer Composition And Location: 1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, synthetic  Maximum Operating Pressure: 5000.0 pounds per square inch  Seat Angle: 37.0 degrees 1st end
Connection Type: Threaded internal tube 1st end Burst Test Pressure: 20000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, synthetic Maximum Operating Pressure: 5000.0 pounds per square inch Seat Angle: 37.0 degrees 1st end
Threaded internal tube 1st end  Burst Test Pressure:  20000.0 pounds per square inch  Layer Composition And Location:  1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, synthetic  Maximum Operating Pressure:  5000.0 pounds per square inch  Seat Angle:  37.0 degrees 1st end
Burst Test Pressure:  20000.0 pounds per square inch  Layer Composition And Location:  1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, synthetic  Maximum Operating Pressure:  5000.0 pounds per square inch  Seat Angle:  37.0 degrees 1st end
20000.0 pounds per square inch  Layer Composition And Location:  1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, synthetic  Maximum Operating Pressure:  5000.0 pounds per square inch  Seat Angle:  37.0 degrees 1st end
Layer Composition And Location:  1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, synthetic  Maximum Operating Pressure:  5000.0 pounds per square inch  Seat Angle:  37.0 degrees 1st end
1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, synthetic  Maximum Operating Pressure:  5000.0 pounds per square inch  Seat Angle:  37.0 degrees 1st end
Maximum Operating Pressure: 5000.0 pounds per square inch Seat Angle: 37.0 degrees 1st end
5000.0 pounds per square inch  Seat Angle:  37.0 degrees 1st end
Seat Angle: 37.0 degrees 1st end
37.0 degrees 1st end
-
Hydrostatic Test Pressure:
10000.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
360.000 inches
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A542a0