Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-363-6797

Cross Sectional Shape:	
Round	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.250 inches	
Tempurature Rating:	
40.0 degrees fahrenheit and 300.0 degrees fahrenheit	single response
Outside Diameter:	
0.580 inches	
Minimum Inside Bending Radius:	
1.750 inches	
Connection Style:	
Swivel, plain 2nd end	
End Connection Design:	
Straight 2nd end	
Connection Type:	
Threaded external pipe 2nd end	
Features Provided:	
Reusable end fittings	
Burst Test Pressure:	
2000.0 pounds per square inch	
Layer Composition And Location:	
1st layer braided textile yarn and 2nd layer braided corr	osion resistant steel wire and outer layer rubber impregnated cotton fabric
Maximum Operating Pressure:	
500.0 pounds per square inch	
Thread Size:	
0.250 inches 1st end	
Inside Surface Condition:	
Smooth	
Measuring Method And Length:	
49.000 inches	
Special Features:	
Used on damper ventilator	
Media For Which Designed:	
Fuel/oil, hydrocarbon single response	
Thread Series Designator:	
Npt 1st end	
Shelf Life:	
N/a	
Unit Of Measure:	

Nonmetallic Hose Assembly - Page 2 of 2

Demilitarization:

No

Fiig:

A542a0

