## NSN 4720-01-363-8029

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-363-8029 **Cross Sectional Shape:** Round **Thread Class:** 2b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.219 inches **Tempurature Rating:** -65.0 degrees fahrenheit and 300.0 degrees fahrenheit single response **Outside Diameter:** 0.461 inches **Minimum Inside Bending Radius:** 2.000 inches **Connection Style:** Swivel nut flare 2nd end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 6000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided corrosion resistant steel wire, partial coverage and outer layer braided corrosion resistant steel wire **Maximum Operating Pressure:** 1500.0 pounds per square inch **Thread Size:** 0.438 inches 1st end Seat Angle: 37.0 degrees 2nd end **Hydrostatic Test Pressure:** 3000.0 pounds per square inch Flow Angle: 90.0 degrees 2nd end **Inside Surface Condition:** Smooth **Measuring Method And Length:** 108.000 inches **Thread Series Designator:** 

N/a

Unf 2nd end Shelf Life:

## NSN 4720-01-363-8029

Nonmetallic Hose Assembly - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A542a0