## NSN 4720-01-363-8031

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-363-8031

Cross Sectional Shape:
Round
Thread Direction:
Right-hand 1st end  Inside Diameter:
0.190 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response
Outside Diameter:
0.520 inches
Minimum Inside Bending Radius:
1.500 inches
Connection Style:
Inverted flare 2nd end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded external tube 2nd end
Burst Test Pressure:
2000.0 pounds per square inch
Layer Composition And Location:
1st layer braided steel wire and outer layer rubber impregnated braided fabric
Maximum Operating Pressure:
500.0 pounds per square inch
Thread Size:
0.250 inches 1st end
Seat Angle:
37.0 degrees 2nd end
Hydrostatic Test Pressure:
1000.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
50.000 inches
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:
Npt 1st end
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 4720-01-363-8031

Nonmetallic Hose Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A542a0