Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-364-4423

Cross Sectional Shape:	
Round	
Thread Class:	
2b 1st end	
Thread Direction:	
Right-hand 1st end	
nside Diameter:	
.375 inches	
Fempurature Rating:	
40.0 degrees fahrenheit and 212.0 degrees fahre	nheit single response
Dutside Diameter:	
1.750 inches	
Ainimum Inside Bending Radius:	
0.500 inches	
Connection Style:	
Swivel nut flare 1st end	
End Connection Design:	
Straight 1st end	
Connection Type:	
Fhreaded internal tube 1st end	
Thready Qty Per Inch (tpi):	
2 1st end	
Burst Test Pressure:	
2000.0 pounds per square inch	
ayer Composition And Location:	
st layer braided corrosion resistant steel wire and	2nd layer braided textile yarn and outer layer molded rubber, synthetic
Maximum Operating Pressure:	
500.0 pounds per square inch	
Fhread Size:	
1.875 inches 1st end	
Seat Angle:	
37.0 degrees 1st end	
lydrostatic Test Pressure:	
000.0 pounds per square inch	
nside Surface Condition:	
Smooth	
Measuring Method And Length:	
65.000 inches	
Media For Which Designed:	
Fuel/oil, hydrocarbon single response	
Thread Series Designator:	
Jn 1st end	

NSN 4720-01-364-4423

Nonmetallic Hose Assembly - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0