Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-364-8720

	I Shape:
Round	
Thread Class:	
3b 1st end	
Thread Directio	n:
Right-hand 1st e	nd
Inside Diamete	:
0.406 inches	
Tempurature R	ating:
-40.0 degrees fa	hrenheit and 212.0 degrees fahrenheit single response
Outside Diame	er:
0.770 inches	
Minimum Inside	Bending Radius:
4.625 inches	
Connection Sty	le:
Swivel nut flare	lst end
End Connectio	n Design:
Straight 1st end	
Connection Ty	e:
Threaded interna	al tube 1st end
Burst Test Pres	sure:
8000.0 pounds p	er square inch
Layer Composi	tion And Location:
1st layer braided	corrosion resistant steel wire and 2nd layer braided textile yarn and outer layer molded rubber, synthetic
Maximum Oper	ating Pressure:
2000.0 pounds p	er square inch
Thread Size:	
0.750 inches 1st	end
Seat Angle:	
37.0 degrees 1s	end
Hydrostatic Tes	
4000.0 pounds p	
Inside Surface	
Smooth	
	nod And Length:
44.000 inches	
Media For Whic	h Designed:
	arbon single response
Thread Series I	
Unf 1st end	
Shelf Life:	
N/a	

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A542a0