## NSN 4720-01-365-2537

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-365-2537

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.750 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 257.0 degrees fahrenheit single response
Outside Diameter:
1.160 inches
Minimum Inside Bending Radius:
9.500 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Reusable end fittings
Thready Qty Per Inch (tpi):
12 1st end
Burst Test Pressure:
9000.0 pounds per square inch
Layer Composition And Location:
1st layer braided corrosion resistant steel wire and 2nd layer braided corrosion resistant steel wire and outer layer molded rubber, synthetic
Maximum Operating Pressure:
2250.0 pounds per square inch
Thread Size:
1.062 inches 1st end
Seat Angle:
37.0 degrees 1st end
Outer Covering Environmental Protection:
Abrasion resistant and weatherproof
Inside Surface Condition:
Smooth
Measuring Method And Length:
48.000 inches

Media For Which Designed: Hydraulic fluid single response

## NSN 4720-01-365-2537

Nonmetallic Hose Assembly - Page 2 of 2



Thread	Series	Des	ignator
Un 1st e	end		

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0