## NSN 4720-01-365-2543

**Cross Sectional Shape:** 

Round

Thread Class: 3b 1st end

**Thread Direction:** 

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-365-2543

Right-hand 1st end
Inside Diameter:
0.280 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 275.0 degrees fahrenheit single response
Outside Diameter:
0.465 inches
Minimum Inside Bending Radius:
0.500 inches
Exterior Color:
Green
End Connection Design:
Straight 1st end
End Fitting Component And Material:
Complete fitting aluminum alloy 6061 all ends
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
20 1st end
Second End Relationship With First End:
Identical
Burst Test Pressure:
1000.0 pounds per square inch
First End Swivel Action Capability:
Not included
Layer Composition And Location:
Outer layer rubber impregnated braided polyamide cord err-100
Maximum Operating Pressure:
250.0 pounds per square inch
Thread Size:
0.4375 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
500.0 pounds per square inch
Outer Covering Environmental Protection:
Abrasion resistant

## NSN 4720-01-365-2543

Nonmetallic Hose Assembly - Page 2 of 2



Inside Surface Condition:
Convoluted
<b>Measuring Method And Length:</b>
11.750 inches
Special Features:
Polyethylene closure both ends
Thread Series Designator:
Un 1st end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

**Fiig:** A542a0