NSN 4720-01-365-7000

Nonmetallic Hose Assembly - Page 1 of 2



Cross Sectional Shape:				
Round				
Thread Class:				
2b 2nd end				
Thread Direction:				
Right-hand 1st end				
Inside Diameter:				
0.500 inches				
Tempurature Rating:				
250.0 degrees fahrenheit single response				
Outside Diameter:				
0.790 inches				
Minimum Inside Bending Radius:				
5.000 inches				
Exterior Color:				
Black				
End Application:				
3810-01-268-1737				
Connection Style:				
Swivel nut, gasket seal 2nd end				
End Connection Design:				
Straight 1st end				
Connection Type:				
Threaded internal tube 1st end				
Features Provided:				
Reusable end fittings				
Burst Test Pressure:				
14000.0 pounds per square inch				
Layer Composition And Location:				
1st layer braided wire and outer layer molded rubber, synthetic				
Maximum Operating Pressure:				
3500.0 pounds per square inch				
Thread Size:				
0.313 inches 2nd end				
Flow Angle:				
90.0 degrees 2nd end				
Inside Surface Condition:				
Smooth				
Measuring Method And Length:				

Media For Which Designed:

Hydraulic fluid, water base single response

NSN 4720-01-365-7000

Nonmetallic Hose Assembly - Page 2 of 2



Thread	Series	Design	nator:
	0000	-00.9.	

Unf 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0