NSN 4720-01-365-7005

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-365-7005

Cross Sectional Shape
Cross Sectional Shape: Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.880 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response
Outside Diameter:
1.240 inches
Minimum Inside Bending Radius:
7.380 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
12 1st end
Burst Test Pressure:
2000.0 pounds per square inch
Layer Composition And Location:
1st layer braided textile yarn and 2nd layer braided textile yarn and outer layer molded rubber, synthetic
Maximum Operating Pressure:
500.0 pounds per square inch
Thread Size:
1.312 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
1000.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
111.500 inches
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:

Un 1st end

NSN 4720-01-365-7005

Nonmetallic Hose Assembly - Page 2 of 2



_				
c	hο	JIF.		ife:
J			_	HG.

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0