

View Online at <https://aerobasegroup.com/nsn/4720-01-366-3733>

Cross Sectional Shape:

Round

Inside Diameter:

0.750 inches

Temperature Rating:

-40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response

Flange Thickness:

0.265 inches 2nd end

Outside Diameter:

1.230 inches

Minimum Inside Bending Radius:

9.500 inches

Center To Center Distance Between Bolt Holes Along Width:

0.800 inches 2nd end

Center To Center Distance Between Bolt Holes Along Length:

1.875 inches 2nd end

Bolt Hole Quantity:

4 2nd end

Flange Length:

2.530 inches and 2.590 inches 2nd end

End Application:

3810-01-268-1737, harnischfeger crane, truck mounted

Flange Width:

1.960 inches 2nd end

Connection Style:

Plain 2nd end

Bolt Hole Diameter:

0.406 inches 2nd end

End Flange Construction:

Solid 2nd end

End Connection Design:

Straight 1st end

Connection Type:

Plain face flange 2nd end

Burst Test Pressure:

12000.0 pounds per square inch

Layer Composition And Location:

1st layer spirally laid steel wire and 2nd layer spirally laid steel wire and 3rd layer spirally laid steel wire and 4th layer spirally laid steel wire and outer layer molded rubber, synthetic

Maximum Operating Pressure:

3000.0 pounds per square inch

Hydrostatic Test Pressure:

6000.0 pounds per square inch

Flow Angle:

90.0 degrees 2nd end

Inside Surface Condition:

Smooth

Measuring Method And Length:

11.375 inches

Flange Style:

Double oval (sae split type flange) 1st end

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0