

View Online at <https://aerobasegroup.com/nsn/4720-01-366-3734>

**Cross Sectional Shape:**

Round

**Inside Diameter:**

0.750 inches

**Temperature Rating:**

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

**Flange Thickness:**

0.315 inches 2nd end

**Outside Diameter:**

1.230 inches

**Minimum Inside Bending Radius:**

9.500 inches

**Angle Between Rigid Elbow Fittings In Deg:**

270.0

**Center To Center Distance Between Bolt Holes Along Width:**

1.093 inches 2nd end

**Center To Center Distance Between Bolt Holes Along Length:**

2.062 inches 2nd end

**Bolt Hole Quantity:**

4 2nd end

**Flange Length:**

2.780 inches 2nd end

**End Application:**

3810-01-268-1737, truck mounted crane

**Flange Width:**

2.310 inches 2nd end

**Connection Style:**

Plain 2nd end

**Bolt Hole Diameter:**

0.406 inches 2nd end

**End Flange Construction:**

Solid 2nd end

**End Connection Design:**

Elbow 2nd end

**Connection Type:**

Plain face flange 2nd end

**Burst Test Pressure:**

12000.0 pounds per square inch

**Layer Composition And Location:**

1st layer braided corrosion resistant steel wire and 2nd layer braided corrosion resistant steel wire and 3rd layer braided corrosion resistant steel wire and 4th layer braided corrosion resistant steel wire and outer layer molded rubber, synthetic

**Maximum Operating Pressure:**

3000.0 pounds per square inch

**Flow Angle:**

90.0 degrees 2nd end

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

24.500 inches

**Flange Style:**

Double oval (sae split type flange) 1st end

**Special Features:**

Crimped fittings

**Media For Which Designed:**

Hydraulic fluid single response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0