NSN 4720-01-366-5548



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-01-366-5548 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.750 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response **Outside Diameter:** 1.230 inches **Minimum Inside Bending Radius:** 6.000 inches **End Application:** 3810-01-268-1737, truck mounted crane **Connection Style:** Swivel nut flare 2nd end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end Thready Qty Per Inch (tpi): 12 2nd end **Burst Test Pressure:** 3000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided textile yarn and 2nd layer braided textile yarn and outer layer molded rubber, synthetic **Maximum Operating Pressure:** 750.0 pounds per square inch **Thread Size:** 1.062 inches 2nd end Seat Angle: 37.0 degrees 2nd end Flow Angle: 45.0 degrees 2nd end

Smooth

Measuring Method

Inside Surface Condition:

Measuring Method And Length:

36.500 inches

Special Features:

Crimped fittings

NSN 4720-01-366-5548

Nonmetallic Hose Assembly - Page 2 of 2



Media	For	Which	Design	ed:

Hydraulic fluid single response

Thread Series Designator:

Un 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0