

View Online at <https://aerobasegroup.com/nsn/4720-01-366-5550>

**Cross Sectional Shape:**

Round

**Inside Diameter:**

0.750 inches

**Temperature Rating:**

-40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response

**Flange Thickness:**

0.265 inches 1st end

**Outside Diameter:**

1.230 inches

**Minimum Inside Bending Radius:**

9.500 inches

**Angle Between Rigid Elbow Fittings In Deg:**

90.0

**Center To Center Distance Between Bolt Holes Along Width:**

0.875 inches 1st end

**Center To Center Distance Between Bolt Holes Along Length:**

1.875 inches 1st end

**Bolt Hole Quantity:**

4 1st end

**Flange Length:**

2.590 inches 1st end

**End Application:**

3810-01-268-1737, truck mounted crane

**Flange Width:**

2.060 inches 1st end

**Connection Style:**

Plain 1st end

**Bolt Hole Diameter:**

0.406 inches 1st end

**End Flange Construction:**

Solid 1st end

**End Connection Design:**

Elbow 1st end

**Connection Type:**

Plain face flange 1st end

**Burst Test Pressure:**

12000.0 pounds per square inch

**Layer Composition And Location:**

1st layer spirally laid steel wire and 2nd layer spirally laid steel wire and 3rd layer spirally laid steel wire and 4th layer spirally laid steel wire and outer layer molded rubber, synthetic

**Maximum Operating Pressure:**

3000.0 pounds per square inch

**Flow Angle:**

90.0 degrees 1st end

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

349.000 inches

**Flange Style:**

Double oval (sae split type flange) 1st end

**Special Features:**

Both ends have crimped flanges, with O-ring, one is weld fitting

**Media For Which Designed:**

Hydraulic fluid single response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0