## NSN 4720-01-366-6097

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-366-6097

| Cross Sectional Shape:  |
|---|
| Round   |
| Thread Class:   |
| 3b 1st end  |
| Thread Direction:   |
| Right-hand 1st end  |
| Inside Diameter:  |
| 0.438 inches  |
| Tempurature Rating:   |
| -65.0 degrees fahrenheit single response and 275.0 degrees fahrenheit single response |
| Outside Diameter:   |
| 0.641 inches  |
| Minimum Inside Bending Radius:  |
| 3.500 inches  |
| Connection Style:   |
| Swivel nut, flareless 2nd end   |
| End Connection Design:  |
| Straight 1st end  |
| Connection Type:  |
| Threaded internal tube 1st end  |
| Burst Test Pressure:  |
| 800.0 pounds per square inch  |
| Layer Composition And Location:   |
| Outer layer braided corrosion resistant steel wire                                    |
| Maximum Operating Pressure:   |
| 200.0 pounds per square inch  |
| Thread Size:  |
| 0.750 inches 2nd end  |
| Seat Angle:   |
| 12.0 degrees 2nd end  |
| Hydrostatic Test Pressure:  |
| 400.0 pounds per square inch  |
| Flow Angle:   |
| 45.0 degrees 2nd end  |
| Inside Surface Condition:   |
| Smooth  |
| Measuring Method And Length:  |
| 15.500 inches   |
| Thread Series Designator:   |
| Unjf 1st end  |
| Shelf Life:   |
| N/a   |

## NSN 4720-01-366-6097

Nonmetallic Hose Assembly - Page 2 of 2



|    | • • |             |    |     |      |
|----|-----|-------------|----|-----|------|
| In | 18  | <i>(</i> )+ | МА | 261 | ıre: |
|    |     |             |    |     |      |

--

Demilitarization:

No

Fiig:

A542a0