NSN 4720-01-366-7174

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-366-7174
Cross Sectional Shape:
Round
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.229 inches
Tempurature Rating:
-100.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response
Outside Diameter:
0.495 inches
Minimum Inside Bending Radius:
3.000 inches
End Application:
3655-00-722-3901
Connection Style:
Plain optional end 1st end
End Connection Design:
Straight 1st end
End Fitting Component And Material:
Complete fitting stainless steel all ends
Fitting Component And Surface Treatment:
Complete fitting passivate 1st end
Connection Type:
Threaded internal pipe 1st end
Features Provided:
Electrostatic discharge capability
Second End Relationship With First End:
Identical
Burst Test Pressure:
24000.0 pounds per square inch
First End Swivel Action Canability:

First End Swivel Action Capability

Not included

Layer Composition And Location:

Outer layer braided corrosion resistant steel wire err-100

Maximum Operating Pressure:

6000.0 pounds per square inch

Thread Size:

0.250 inches 1st end

Inside Surface Condition:

Smooth

Measuring Method And Length:

24.000 inches excluding end fittings

NSN 4720-01-366-7174

Nonmetallic Hose Assembly - Page 2 of 2



Spe	cial	Features	s:

Cga cylinder connection

Thread Series Designator:

Npt 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0