## NSN 4720-01-366-9030

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-366-9030 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.380 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response **Outside Diameter:** 0.750 inches **Minimum Inside Bending Radius:** 4.000 inches **End Application:** 3810-01-268-1737 **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 2nd end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 4500.0 pounds per square inch **Layer Composition And Location:** 1st layer braided textile yarn and outer layer molded rubber, synthetic **Maximum Operating Pressure:** 1125.0 pounds per square inch **Thread Size:** 0.562 inches 1st end Seat Angle: 37.0 degrees 1st end **Hydrostatic Test Pressure:** 2250.0 pounds per square inch Flow Angle: 90.0 degrees 1st end **Outer Covering Environmental Protection:** Abrasion resistant **Inside Surface Condition:** 

Smooth

**Measuring Method And Length:** 

60.000 inches

## NSN 4720-01-366-9030

Nonmetallic Hose Assembly - Page 2 of 2



N	Λ	edia	For	Which	Design	ed

Fuel/oil, hydrocarbon single response

**Thread Series Designator:** 

Unf 1st end

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

Demilitarization:

No

Fiig:

A542a0