## NSN 4720-01-367-9983

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-367-9983			
Cross Sectional Shape:			
Round			
Thread Class:			
2b 1st end			
Thread Direction:			
Right-hand 1st end			
Inside Diameter:			
0.880 inches			
Tempurature Rating:			
-100.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response			
Outside Diameter:			
1.030 inches			
Minimum Inside Bending Radius:			
9.000 inches			
End Application:			
2320-01-318-9902 het (heavy equipment transporter)			
Connection Style:			
Swivel nut flare 2nd end			
End Connection Design:			
Straight 1st end			
Connection Type:			
Threaded internal tube 1st end			
Thready Qty Per Inch (tpi):			
12 2nd end			
Burst Test Pressure:			
4000.0 pounds per square inch			
Layer Composition And Location:			
Outer layer braided corrosion resistant steel wire			
Maximum Operating Pressure:			
1000.0 pounds per square inch			
Thread Size:			
1.312 inches 2nd end			
Seat Angle:			

37.0 degrees 2nd end

**Hydrostatic Test Pressure:** 

2000.0 pounds per square inch

Flow Angle:

90.0 degrees 2nd end

**Inside Surface Condition:** 

Smooth

**Measuring Method And Length:** 

112.000 inches

## NSN 4720-01-367-9983

Nonmetallic Hose Assembly - Page 2 of 2



Thread S	Series	Designator:
----------	--------	-------------

Un 2nd end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0