

View Online at <https://aerobasegroup.com/nsn/4720-01-368-7559>

**Cross Sectional Shape:**

Round

**Inside Diameter:**

1.375 inches

**Temperature Rating:**

-65.0 degrees fahrenheit and 300.0 degrees fahrenheit single response

**Flange Thickness:**

0.495 inches 2nd end

**Outside Diameter:**

1.735 inches

**Minimum Inside Bending Radius:**

9.000 inches

**Angle Between Rigid Elbow Fittings In Deg:**

355.0

**Flange Outside Diameter:**

2.375 inches 2nd end

**Connection Style:**

Raised swivel w/ gasket groove 2nd end

**Raised Face Diameter:**

1.250 inches 2nd end

**End Flange Construction:**

Solid 2nd end

**End Connection Design:**

Elbow 2nd end

**Connection Type:**

Raised face flange 2nd end

**Burst Test Pressure:**

2000.0 pounds per square inch

**Layer Composition And Location:**

1st layer braided corrosion resistant steel wire, partial coverage and outer layer braided corrosion resistant steel wire

**Maximum Operating Pressure:**

250.0 pounds per square inch

**Hydrostatic Test Pressure:**

800.0 pounds per square inch

**Flow Angle:**

90.0 degrees 2nd end

**Outer Covering Environmental Protection:**

Corrosion resistant

**Criticality Code Justification:**

Feat

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

22.250 inches

**Flange Style:**

Round w/ out bolt holes 2nd end

**Special Features:**

Flight safety critical item

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0