## NSN 4720-01-368-8166

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-368-8166

Cross Sectional Shape:
Round
Thread Class:
3a 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.375 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 160.0 degrees fahrenheit single response
Outside Diameter:
0.594 inches
Minimum Inside Bending Radius:
4.000 inches
Exterior Color:
Black
Quick Disconnect Size:
0.625 inches 1st end
End Application:
4920-01-322-3712
Connection Style:
Duch (automal) 1st and
Push (external) 1st end
End Connection Design:
End Connection Design:
End Connection Design: Straight 1st end
End Connection Design: Straight 1st end Connection Type:
End Connection Design: Straight 1st end Connection Type: External quick disconnect 1st end
End Connection Design: Straight 1st end Connection Type: External quick disconnect 1st end Burst Test Pressure:
End Connection Design: Straight 1st end Connection Type: External quick disconnect 1st end Burst Test Pressure: 1000.0 pounds per square inch
End Connection Design: Straight 1st end Connection Type: External quick disconnect 1st end Burst Test Pressure: 1000.0 pounds per square inch Layer Composition And Location:
End Connection Design: Straight 1st end Connection Type: External quick disconnect 1st end Burst Test Pressure: 1000.0 pounds per square inch Layer Composition And Location: 1st layer braided cotton cord and outer layer molded rubber, synthetic
End Connection Design: Straight 1st end Connection Type: External quick disconnect 1st end Burst Test Pressure: 1000.0 pounds per square inch Layer Composition And Location: 1st layer braided cotton cord and outer layer molded rubber, synthetic Maximum Operating Pressure:
End Connection Design: Straight 1st end Connection Type: External quick disconnect 1st end Burst Test Pressure: 1000.0 pounds per square inch Layer Composition And Location: 1st layer braided cotton cord and outer layer molded rubber, synthetic Maximum Operating Pressure: 150.0 pounds per square inch
End Connection Design: Straight 1st end Connection Type: External quick disconnect 1st end Burst Test Pressure: 1000.0 pounds per square inch Layer Composition And Location: 1st layer braided cotton cord and outer layer molded rubber, synthetic Maximum Operating Pressure: 150.0 pounds per square inch Thread Size:
End Connection Design: Straight 1st end Connection Type: External quick disconnect 1st end Burst Test Pressure: 1000.0 pounds per square inch Layer Composition And Location: 1st layer braided cotton cord and outer layer molded rubber, synthetic Maximum Operating Pressure: 150.0 pounds per square inch Thread Size: 0.438 inches 1st end
End Connection Design: Straight 1st end Connection Type: External quick disconnect 1st end Burst Test Pressure: 1000.0 pounds per square inch Layer Composition And Location: 1st layer braided cotton cord and outer layer molded rubber, synthetic Maximum Operating Pressure: 150.0 pounds per square inch Thread Size: 0.438 inches 1st end Hydrostatic Test Pressure:
End Connection Design: Straight 1st end Connection Type: External quick disconnect 1st end Burst Test Pressure: 1000.0 pounds per square inch Layer Composition And Location: 1st layer braided cotton cord and outer layer molded rubber, synthetic Maximum Operating Pressure: 150.0 pounds per square inch Thread Size: 0.438 inches 1st end Hydrostatic Test Pressure: 300.0 pounds per square inch
End Connection Design: Straight 1st end Connection Type: External quick disconnect 1st end Burst Test Pressure: 1000.0 pounds per square inch Layer Composition And Location: 1st layer braided cotton cord and outer layer molded rubber, synthetic Maximum Operating Pressure: 150.0 pounds per square inch Thread Size: 0.438 inches 1st end Hydrostatic Test Pressure: 300.0 pounds per square inch Inside Surface Condition:
End Connection Design: Straight 1st end Connection Type: External quick disconnect 1st end Burst Test Pressure: 1000.0 pounds per square inch Layer Composition And Location: 1st layer braided cotton cord and outer layer molded rubber, synthetic Maximum Operating Pressure: 150.0 pounds per square inch Thread Size: 0.438 inches 1st end Hydrostatic Test Pressure: 300.0 pounds per square inch Inside Surface Condition: Smooth

Pitot test hose assembly., f-16 aircraft

## NSN 4720-01-368-8166

Nonmetallic Hose Assembly - Page 2 of 2



Media	For	Which	Design	ed:

Propane single response

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0