Nonmetallic Hose Assembly - Page 1 of 1

View Online at https://aerobasegroup.com/nsn/4720-01-368-8513



Round Inside Diameter: 0.250 inches Inside Diameter: 0.250 inches Outside Diameter: 0.450 inches Outside Diameter: 0.450 inches Outside Diameter: 0.450 inches Outside Diameter: 0.450 inches Outside Diameter: 0.500 inches Outside Diameter: 0.500 inches Outside Diameter: 0.500 inches Outside Diameter: 0.500 inches Outside Diameter: 500.0 pounds per square inch Outside Diameter: 500.0 pounds per square	Cross Sectional Shape:	
Inside Diameter: 0.250 inches  Tempurature Rating: 275.0 degrees fahrenheit single response Outside Diameter: 0.450 inches Minimum Inside Bending Radius: 0.500 inches Monection Style: Swivel nut flare 1st end Connection Style: Swivel nut flare 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 500.0 pounds per square inch Maximum Operating Pressure: 250.0 pounds per square inch Seat Angle: 37.0 degrees 1st end Inside Surface Condition: Convoluted Measuring Method And Length: 18.000 inches Thread Series Designator: Unjf 1st end Shelf Life: N/a Unit Of Measure: T Pomilitarization: No		
0.250 inches Tempurature Rating: 275.0 degrees fahrenheit single response Outside Diameter: 0.450 inches Minimun Inside Bending Radius: 0.500 inches Connection Style: Swivel nut flare 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 500.0 pounds per square inch Maximun Operating Pressure: 250.0 pounds per square inch Seat Angle: 37.0 degrees 1st end Inside Surface Condition: Convoluted Measuring Method And Length: 18.000 inches Thread Series Designator: Unjf 1st end Shelf Life: Na  In in Commension In inches Internal Internatio Internal Internal Internatio Internal Internatio Internal Internatio Internal In		
Tempurature Rating:         275.0 degrees fahrenheit single response         Outside Diameter:         0.450 inches         Minimum Inside Bending Radius:         0.500 inches         Connection Style:         Swivel nut flare 1st end         Connection Type:         Threaded internal tube 1st end         Burst Test Pressure:         500.0 pounds per square inch         Maximum Operating Pressure:         250.0 pounds per square inch         Stold grees 1st end         Inside Surface Condition:         Convoluted         Measuring Method And Length:         18.000 inches         Thread Series Designator:         Unjf 1st end         Shelf Life:         Na         Unif Of Measure:            Demilitarization:         No		
275.0 degrees fahrenheit single response Outside Diameter: 0.450 inches Minimum Inside Bending Radius: 0.500 inches Connection Style: Swivel nut flare 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 500.0 pounds per square inch Maximum Operating Pressure: 250.0 pounds per square inch Seat Angle: 37.0 degrees 1st end Inside Surface Condition: Convoluted Measuring Method And Length: 18.000 inches Thread Series Designator: Unjf 1st end Sheff Life: N/a Unit Of Measure:  Demilitarization: No		
Outside Diameter:         0.450 inches         Minimum Inside Bending Radius:         0.500 inches         Connection Style:         Swivel nut flare 1st end         Connection Type:         Threaded internal tube 1st end         Burst Test Pressure:         500.0 pounds per square inch         Maximum Operating Pressure:         250.0 pounds per square inch         Seat Angle:         37.0 degrees 1st end         Inside Surface Condition:         Convoluted         Measuring Method And Length:         18.000 inches         Thread Series Designator:         Unjf 1st end         Shelf Life:         N/a         Unit Of Measure:            Demilitarization:         No		
0.450 inches Minimum Inside Bending Radius: 0.500 inches Connection Style: Swivel nut flare 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 500.0 pounds per square inch Maximum Operating Pressure: 250.0 pounds per square inch Seat Angle: 37.0 degrees 1st end Inside Surface Condition: Convoluted Measuring Method And Length: 18.000 inches Thread Series Designator: Unjf 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No		
Minimum Inside Bending Radius:       0.500 inches         0.500 inches       Connection Style:         Swivel nut flare 1st end       Connection Type:         Threaded internal tube 1st end       Burst Test Pressure:         500.0 pounds per square inch       Maximum Operating Pressure:         250.0 pounds per square inch       Seat Angle:         37.0 degrees 1st end       Inside Surface Condition:         Convoluted       Measuring Method And Length:         18.000 inches       Thread Series Designator:         Unif 1st end       Shelf Life:         N/a       Unif 1st end         Diff Measure:       Image:         N/a       Image:         N/a       Image:         N/a       Image:         Image:       Image:      Image:       Image:		
0.500 inches Connection Style: Swivel nut flare 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 500.0 pounds per square inch Maximum Operating Pressure: 250.0 pounds per square inch Seat Angle: 37.0 degrees 1st end Inside Surface Condition: Convoluted Measuring Method And Length: 18.000 inches Thread Series Designator: Unijf 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No		
Connection Style: Swivel nut flare 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 500.0 pounds per square inch Maximum Operating Pressure: 250.0 pounds per square inch Seat Angle: 37.0 degrees 1st end Inside Surface Condition: Convoluted Measuring Method And Length: 18.000 inches Thread Series Designator: Unif 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No		
Swivel nut flare 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 500.0 pounds per square inch Maximum Operating Pressure: 250.0 pounds per square inch Seat Angle: 37.0 degrees 1st end Inside Surface Condition: Convoluted Measuring Method And Length: 18.000 inches Thread Series Designator: Unif 1st end Shelf Life: Na Unit Of Measure:  Demilitarization: No		
Connection Type: Threaded internal tube 1st end Burst Test Pressure: 500.0 pounds per square inch Maximum Operating Pressure: 250.0 pounds per square inch Seat Angle: 37.0 degrees 1st end Inside Surface Condition: Convoluted Measuring Method And Length: 18.000 inches Thread Series Designator: Unif 1st end Shelf Life: N/a Unit Of Measure:  Demilitarization: No		
Threaded internal tube 1st end Burst Test Pressure: 500.0 pounds per square inch Maximum Operating Pressure: 250.0 pounds per square inch Seat Angle: 37.0 degrees 1st end Inside Surface Condition: Convoluted Measuring Method And Length: 18.000 inches Thread Series Designator: Unit of the sure: N/a Unit of Measure:  Demilitarization: No		
500.0 pounds per square inch Maximum Operating Pressure: 250.0 pounds per square inch Seat Angle: 37.0 degrees 1st end 37.0 degrees 1st end Inside Surface Condition: Convoluted Measuring Method And Length: 18.000 inches Thread Series Designator: Unjf 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No		
Maximum Operating Pressure:250.0 pounds per square inchSeat Angle:37.0 degrees 1st endInside Surface Condition:ConvolutedMeasuring Method And Length:18.000 inchesThread Series Designator:Unjf 1st endShelf Life:N/aUnit Of Measure:Demilitarization:No	Burst Test Pressure:	
250.0 pounds per square inch Seat Angle: 37.0 degrees 1st end Inside Surface Condition: Convoluted Measuring Method And Length: 18.000 inches Thread Series Designator: Unjf 1st end Shelf Life: N/a Unit Of Measure:  Demilitarization: No	500.0 pounds per square inch	
Seat Angle: 37.0 degrees 1st end Inside Surface Condition: Convoluted Measuring Method And Length: 18.000 inches Thread Series Designator: Unjf 1st end Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Maximum Operating Pressure:	
37.0 degrees 1st end Inside Surface Condition: Convoluted Measuring Method And Length: 18.000 inches Thread Series Designator: Unjf 1st end Shelf Life: N/a Unit Of Measure:  Demilitarization: No	250.0 pounds per square inch	
Inside Surface Condition: Convoluted Measuring Method And Length: 18.000 inches Thread Series Designator: Unjf 1st end Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Seat Angle:	
Convoluted Measuring Method And Length: 18.000 inches Thread Series Designator: Unif 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No	37.0 degrees 1st end	
Measuring Method And Length: 18.000 inches Thread Series Designator: Unif 1st end Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Inside Surface Condition:	
18.000 inches Thread Series Designator: Unif 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No	Convoluted	
Thread Series Designator:   Unif 1st end   Shelf Life:   N/a   Unit Of Measure:     Demilitarization:   No	Measuring Method And Length:	
Unjf 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No	18.000 inches	
Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Thread Series Designator:	
N/a Unit Of Measure:  Demilitarization: No	Unjf 1st end	
Unit Of Measure:  Demilitarization: No	Shelf Life:	
 Demilitarization: No	N/a	
Demilitarization: No	Unit Of Measure:	
No		
	Demilitarization:	
Fiig:	No	
	Fiig:	