## NSN 4720-01-368-9708



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-01-368-9708 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.375 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response **Outside Diameter:** 0.690 inches **Minimum Inside Bending Radius:** 3.500 inches **Exterior Color:** Blue **End Application:** 3810-01-268-1737, truck mounted crane **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 2nd end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 16000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided corrosion resistant steel wire and outer layer molded rubber, ethylene propylene **Maximum Operating Pressure:** 4000.0 pounds per square inch **Thread Size:** 0.562 inches 2nd end Seat Angle: 37.0 degrees 1st end **Inside Surface Condition:** Smooth **Measuring Method And Length:** 148.000 inches **Special Features:** Crimped fittings

Unf 2nd end

**Thread Series Designator:** 

## NSN 4720-01-368-9708

Nonmetallic Hose Assembly - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0