Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-369-2032

Cross S	ectional Shape:
Round	
Thread	Class:
2b 1st er	nd
Thread	Direction:
Right-ha	nd 1st end
Inside D	iameter:
0.406 ind	ches
Tempura	ature Rating:
-65.0 de	grees fahrenheit single response and 450.0 degrees fahrenheit single response
Outside	Diameter:
0.549 ind	ches
Minimur	n Inside Bending Radius:
5.200 ind	ches
Connect	tion Style:
Swivel n	ut flare 1st end
End Cor	nnection Design:
Straight	1st end
Connect	tion Type:
Threade	d internal tube 1st end
Burst Te	est Pressure:
10000.0	pounds per square inch
Layer C	omposition And Location:
Outer lay	ver braided corrosion resistant steel wire
Maximu	m Operating Pressure:
2000.0 p	ounds per square inch
Thread \$	Size:
0.750 ind	ches 1st end
Seat An	gle:
37.0 deg	rees 1st end
Inside S	urface Condition:
Smooth	
Measuri	ng Method And Length:
30.000 ir	nches
Thread \$	Series Designator:
Unf 1st e	end
Shelf Lif	fe:
N/a	
Unit Of I	Measure:
Demilita	rization:
No	

NSN 4720-01-369-2032

Nonmetallic Hose Assembly - Page 2 of 2

Fiig: A542a0

