NSN 4720-01-369-3543

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-369-3543

Cross Sectional Shape:		
Round		
Thread Class:		
2b 1st end		
Thread Direction:		
Right-hand 1st end		
Inside Diameter:		
0.380 inches		
Tempurature Rating:		
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response		
Outside Diameter:		
0.840 inches		
Minimum Inside Bending Radius:		
3.500 inches		
End Application:		
3810-01-268-1737		
Connection Style:		
Swivel nut flare 2nd end		
End Connection Design:		
Straight 2nd end		
Connection Type:		
Threaded internal tube 1st end		
Features Provided:		
Reusable end fittings		
Burst Test Pressure:		
16000.0 pounds per square inch		
Layer Composition And Location:		
1st layer braided wire and outer layer molded rubber, synthetic		
Maximum Operating Pressure:		
4000.0 pounds per square inch		
Thread Size:		
0.750 inches 1st end		
Seat Angle:		
37.0 degrees 2nd end		
Hydrostatic Test Pressure:		
8000.0 pounds per square inch		
Inside Surface Condition:		
Smooth		
Measuring Method And Length:		
56.000 inches		
Media For Which Designed:		

Fuel/oil, hydrocarbon single response

NSN 4720-01-369-3543

Nonmetallic Hose Assembly - Page 2 of 2



		_
Thread	Series	Designator:

Unf 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0