

View Online at <https://aerobasegroup.com/nsn/4720-01-369-3544>

Cross Sectional Shape:

Round

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.406 inches

Temperature Rating:

-58.0 degrees fahrenheit single response and 302.0 degrees fahrenheit single response

Outside Diameter:

0.770 inches

Minimum Inside Bending Radius:

1.750 inches

Hose Or Tubing Specification/std Data:

Sae j1402-81343 standard (includes industry or association standards, individual manufactureer standards, etc.).

End Application:

3810-01-268-1737

Connection Style:

Swivel, plain 1st end

End Connection Design:

Straight 2nd end

End Fitting Component And Material:

Complete fitting steel all ends

Connection Type:

Threaded external pipe 2nd end

Second End Relationship With First End:

Not identical

Burst Test Pressure:

2000.0 pounds per square inch

First End Swivel Action Capability:

Included

Layer Composition And Location:

1st layer braided textile yarn err-100

Maximum Operating Pressure:

500.0 pounds per square inch

Thread Size:

0.375 inches 1st end

Inside Surface Condition:

Smooth

Measuring Method And Length:

100.000 inches

Second End Swivel Action Capability:

Not included

Special Features:

Inner conveying tube material-rubber, synthetic

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Nptf 2nd end

Specification Data:

Sae j1402-81343 national std/spec

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0