NSN 4720-01-369-4035

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-369-4035

Cross Sectional Shape:
Round
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.411 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response
Outside Diameter:
0.810 inches
Minimum Inside Bending Radius:
2.310 inches
Exterior Color:
Black
End Application:
3810-01-268-1737, truck mounted crane
Connection Style:
Swivel, plain 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded external pipe 1st end
Burst Test Pressure:
2000.0 pounds per square inch
Layer Composition And Location:
1st layer braided corrosion resistant steel wire and 2nd layer braided textile yarn and outer layer braided textile yarn
Maximum Operating Pressure:
500.0 pounds per square inch
Thread Size:
0.375 inches 1st end
Outer Covering Environmental Protection:
Heat resistant and oil resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
77.000 inches
Special Features:
Non-detachable fittings
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:

Npt 1st end

NSN 4720-01-369-4035

Nonmetallic Hose Assembly - Page 2 of 2



_				
c	hο	.1+		ife:
J	116		_	HG.

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0