NSN 4720-01-369-6465

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-369-6465
Cross Sectional Shape:
Round
Inside Diameter:
1.500 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Flange Thickness:
0.315 inches 1st end
Outside Diameter:
2.060 inches
Minimum Inside Bending Radius:
20.000 inches
Center To Center Distance Between Bolt Holes Along Width:
1.437 inches 1st end
Center To Center Distance Between Bolt Holes Along Length:
2.750 inches 1st end
Bolt Hole Quantity:
4 1st end
Flange Length:
3.720 inches 1st end
End Application:
3810-01-268-1737
Flange Width:
1.580 inches 1st end
Connection Style:
Plain swivel 1st end
Bolt Hole Diameter:
0.531 inches 1st end
End Flange Construction:
Split 1st end
End Connection Design:
Straight 1st end
Connection Type:
Plain face flange 1st end
Burst Test Pressure:
2000.0 pounds per square inch
Layer Composition And Location:
1st layer braided wire and outer layer wrapped rubber, synthetic
Maximum Operating Pressure:

700.0 pounds per square inch **Hydrostatic Test Pressure:**

1400.0 pounds per square inch

NSN 4720-01-369-6465

Nonmetallic Hose Assembly - Page 2 of 2



Flow Angle:
90.0 degrees 2nd end
Inside Surface Condition:
Smooth
Measuring Method And Length:
15.500 inches
Flange Style:
Double oval (sae split type flange) 1st end
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A542a0