NSN 4720-01-369-6467

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-369-6467

One of Oceanies of Observer
Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
1.000 inches
Tempurature Rating:
-40.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response
Outside Diameter:
1.560 inches
Minimum Inside Bending Radius:
11.000 inches
Hose Or Tubing Specification/std Data:
Sae j517, 100r9, type a-81343 standard (includes industry or association standards, individual manufactureer standards, etc.).
First End Fitting Specification/std Data:
Fc9515-16-16s standard (includes industry or association standards, individual manufactureer standards, etc.).
End Connection Design:
Straight 1st end
End Fitting Component And Material:
Complete fitting stainless steel all ends
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
12 1st end
Second End Relationship With First End:
Identical
Burst Test Pressure:
12000.0 pounds per square inch
First End Swivel Action Capability:
Included
Layer Composition And Location:
Outer layer wrapped rubber, synthetic err-100
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
1.312 inches 1st end
Seat Angle:
37.0 degrees 1st end

Abrasion resistant

Outer Covering Environmental Protection:

NSN 4720-01-369-6467

Nonmetallic Hose Assembly - Page 2 of 2



Inside Surface Condition:
Smooth
Measuring Method And Length:
40.000 inches
Special Features:
Inner conveying tube material-rubber, synthetic
Media For Which Designed:
Hydraulic fluid single response
Thread Series Designator:
Un 1st end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A542a0