## NSN 4720-01-369-9055

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-369-9055

Cross Sectional Shape:				
Round				
Thread Class:				
2b 1st end				
Thread Direction:				
Right-hand 1st end				
Inside Diameter:				
0.250 inches				
Tempurature Rating:				
-40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response				
Outside Diameter:				
0.530 inches				
Minimum Inside Bending Radius:				
4.000 inches				
End Application:				
3930-01-330-8907, fork lift truck				
Connection Style:				
Swivel nut flare 1st end				
End Connection Design:				
Straight 2nd end				
Connection Type:				
Threaded internal tube 1st end				
Burst Test Pressure:				
11000.0 pounds per square inch				
Layer Composition And Location:				
1st layer braided wire and outer layer molded rubber, synthetic				
Maximum Operating Pressure:				
2750.0 pounds per square inch				
Thread Size:				
0.438 inches 1st end				
Seat Angle:				
37.0 degrees 2nd end				
Hydrostatic Test Pressure:				
5500.0 pounds per square inch				
Flow Angle:				
90.0 degrees 1st end				
Inside Surface Condition:				
Smooth				
Measuring Method And Length:				
74.000 inches				
Media For Which Designed:				

Fuel/oil, hydrocarbon single response

## NSN 4720-01-369-9055

Nonmetallic Hose Assembly - Page 2 of 2



_	brood	Carias	Docionatori
ı	meau	Series	Designator:

Unf 2nd end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0