NSN 4720-01-369-9070

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-369-9070

00
Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.375 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
0.780 inches
Minimum Inside Bending Radius:
5.000 inches
End Application:
Forklift, hyster co.
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
9000.0 pounds per square inch
Layer Composition And Location:
1st layer braided wire and outer layer wrapped rubber, synthetic
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
0.562 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
6000.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
96.000 inches
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:

Unf 1st end

NSN 4720-01-369-9070

Nonmetallic Hose Assembly - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J	116		_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0