## NSN 4720-01-370-0184

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-370-0184

Cross Sectional Shape:
Round
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.188 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 302.0 degrees fahrenheit single response
Outside Diameter:
0.520 inches
Minimum Inside Bending Radius:
3.000 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Reusable end fittings
Burst Test Pressure:
12000.0 pounds per square inch
Layer Composition And Location:
1st layer braided textile yarn and 2nd layer braided steel wire and outer layer braided textile yarn
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Seat Angle:
37.0 degrees 1st end
Inside Surface Condition:
Smooth
Measuring Method And Length:
13.500 inches
Media For Which Designed:
Air and fuel/oil, hydrocarbon and hydraulic fluid, water base single response
Thread Series Designator:
Jic 1st end
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 4720-01-370-0184

Nonmetallic Hose Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A542a0