Nonmetallic Hose Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-01-370-6023

| Cross Sectional Shape:  |   |
|---|---|
| Round   |   |
| Thread Class:   |   |
| 2b 1st end  |   |
| Thread Direction:   |   |
| Right-hand 1st end  |   |
| Inside Diameter:  |   |
| 0.250 inches  |   |
| Tempurature Rating:   |   |
| -65.0 degrees fahrenheit and 450.0 degrees fahrenheit single response | 9 |
| Outside Diameter:   |   |
| 0.343 inches  |   |
| Connection Style:   |   |
| Swivel nut flare 1st end  |   |
| End Connection Design:  |   |
| Straight 1st end  |   |
| Connection Type:  |   |
| Threaded internal tube 1st end  |   |
| Burst Test Pressure:  |   |
| 7000.0 pounds per square inch   |   |
| Layer Composition And Location:                                       |   |
| 1st layer braided steel wire and outer layer molded rubber, synthetic |   |
| Maximum Operating Pressure:   |   |
| 1500.0 pounds per square inch   |   |
| Thread Size:  |   |
| 0.562 inches 1st end  |   |
| Seat Angle:   |   |
| 45.0 degrees 1st end  |   |
| Inside Surface Condition:   |   |
| Smooth  |   |
| Measuring Method And Length:  |   |
| 28.000 inches   |   |
| Thread Series Designator:   |   |
| Unf 1st end   |   |
| Shelf Life:   |   |
| N/a   |   |
| Unit Of Measure:  |   |
|   |   |
| Demilitarization:   |   |
| No  |   |
| Fiig:   |   |
| A542a0  |   |