

View Online at <https://aerobasegroup.com/nsn/4720-01-370-6031>

Cross Sectional Shape:

Round

Inside Diameter:

2.000 inches

Temperature Rating:

-40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

Flange Thickness:

1.500 inches 1st end

Outside Diameter:

2.680 inches

Minimum Inside Bending Radius:

25.000 inches

Center To Center Distance Between Bolt Holes Along Width:

1.750 inches 1st end

Center To Center Distance Between Bolt Holes Along Length:

3.810 inches 1st end

Bolt Hole Quantity:

4 1st end

Flange Length:

4.000 inches 1st end

Flange Width:

4.480 inches 1st end

Connection Style:

Plain w/ gasket groove (sae flanged head) 1st end

Bolt Hole Diameter:

0.780 inches 1st end

End Flange Construction:

Solid 1st end

End Connection Design:

Elbow 1st end

Connection Type:

Plain face flange 1st end

Features Provided:

Reusable end fittings

Burst Test Pressure:

12000.0 pounds per square inch

Layer Composition And Location:

1st layer spirally laid steel wire and 2nd layer spirally laid steel wire and 3rd layer spirally laid steel wire and 4th layer spirally laid steel wire and outer layer wrapped rubber, synthetic

Maximum Operating Pressure:

3000.0 pounds per square inch

Hydrostatic Test Pressure:

6000.0 pounds per square inch

Flow Angle:

90.0 degrees 1st end

Inside Surface Condition:

Smooth

Measuring Method And Length:

96.000 inches

Flange Style:

Double oval (sae split type flange) 1st end

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0