NSN 4720-01-370-6449

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-370-6449 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.500 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response **Outside Diameter:** 0.790 inches **Minimum Inside Bending Radius:** 5.000 inches **End Application:** 3810-01-268-1737 **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 14000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided wire and outer layer wrapped rubber, synthetic **Maximum Operating Pressure:** 3500.0 pounds per square inch **Thread Size:** 0.750 inches 2nd end Seat Angle: 37.0 degrees 1st end Flow Angle: 90.0 degrees 2nd end **Outer Covering Environmental Protection:** Abrasion resistant **Inside Surface Condition:** Smooth **Measuring Method And Length:** 72.000 inches

Special Features:

Permanent fittings both ends

NSN 4720-01-370-6449

Nonmetallic Hose Assembly - Page 2 of 2



| N | Λ | edia | For | Which | Design | ed |
|---|---|------|-----|-------|--------|----|
| | | | | | | |

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unf 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0