Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-371-1316

Cross Sectional Shape:
Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
1.250 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response
Outside Diameter:
2.000 inches
Minimum Inside Bending Radius:
16.500 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Reusable end fittings
Thready Qty Per Inch (tpi):
12 1st end
Burst Test Pressure:
6500.0 pounds per square inch
Layer Composition And Location:
1st layer braided wire and 2nd layer braided wire and outer layer molded rubber, synthetic
Maximum Operating Pressure:
1625.0 pounds per square inch
Thread Size:
1.875 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
3450.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
96.000 inches
Media For Which Designed:
Fuel/oil, hydrocarbon single response

Nonmetallic Hose Assembly - Page 2 of 2

Thread Series Designator:

Un 1st end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0

