## NSN 4720-01-371-1318



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-01-371-1318 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 1.500 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response **Outside Diameter:** 2.250 inches **Minimum Inside Bending Radius:** 20.000 inches **End Application:** Hyd. Power unit, jered brown bros. Inc. **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end Thready Qty Per Inch (tpi): 12 1st end **Burst Test Pressure:** 5000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided steel wire and 2nd layer braided steel wire and outer layer braided textile yarn **Maximum Operating Pressure:** 1250.0 pounds per square inch **Thread Size:** 1.875 inches 1st end Seat Angle: 37.0 degrees 1st end **Hydrostatic Test Pressure:** 2500.0 pounds per square inch

**Outer Covering Environmental Protection:** 

Abrasion resistant

**Inside Surface Condition:** 

Smooth

**Measuring Method And Length:** 

51.000 inches

## NSN 4720-01-371-1318

Nonmetallic Hose Assembly - Page 2 of 2



Media	For	Which	Design	ed

Fuel/oil, hydrocarbon single response

**Thread Series Designator:** 

Un 1st end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0