

View Online at <https://aerobasegroup.com/nsn/4720-01-371-1324>

**Cross Sectional Shape:**

Round

**Inside Diameter:**

2.000 inches

**Tempurature Rating:**

-40.0 degrees fahrenheit single response and 250.0 degrees fahrenheit single response

**Bolt Circle Diameter:**

0.530 inches 1st end

**Flange Thickness:**

1.500 inches 1st end

**Outside Diameter:**

2.680 inches

**Minimum Inside Bending Radius:**

25.000 inches

**Angle Between Rigid Elbow Fittings In Deg:**

0.0

**Hose Or Tubing Specification/std Data:**

Sae j517, 100r1, fc254 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Center To Center Distance Between Bolt Holes Along Width:**

1.250 inches 1st end

**Bolt Hole Quantity:**

4 1st end

**Flange Length:**

1.525 inches 1st end

**End Application:**

Hyd.Power unit, jered brown bros.Inc.

**Flange Width:**

3.030 inches 1st end

**Connection Style:**

Raised 1st end

**Bolt Hole Diameter:**

0.530 inches 1st end

**Raised Face Height:**

0.025 inches 1st end

**Raised Face Diameter:**

2.120 inches 1st end

**End Flange Construction:**

Solid 1st end

**End Connection Design:**

Elbow 1st end

**End Fitting Component And Material:**

Complete fitting steel all ends

**Connection Type:**

Raised face flange 1st end

**Burst Test Pressure:**

12000.0 pounds per square inch

**First End Swivel Action Capability:**

Not included

**Layer Composition And Location:**

Outer layer wrapped rubber, synthetic err-100

**Maximum Operating Pressure:**

3000.0 pounds per square inch

**Hydrostatic Test Pressure:**

6000.0 pounds per square inch

**Flow Angle:**

90.0 degrees 1st end

**Outer Covering Environmental Protection:**

Abrasion resistant

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

72.000 inches

**Flange Style:**

Oval 1st end

**Special Features:**

Inner conveying tube material-rubber, synthetic

**Media For Which Designed:**

Hydraulic fluid single response

**Specification Data:**

Sae j517, 100r1, fc254 national std/spec

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0