

View Online at <https://aerobasegroup.com/nsn/4720-01-371-1324>

Cross Sectional Shape:

Round

Inside Diameter:

2.000 inches

Temperature Rating:

-40.0 degrees fahrenheit single response and 250.0 degrees fahrenheit single response

Bolt Circle Diameter:

0.530 inches 1st end

Flange Thickness:

1.500 inches 1st end

Outside Diameter:

2.680 inches

Minimum Inside Bending Radius:

25.000 inches

Angle Between Rigid Elbow Fittings In Deg:

0.0

Hose Or Tubing Specification/std Data:

Sae j517, 100r1, fc254 standard (includes industry or association standards, individual manufactureer standards, etc.).

Center To Center Distance Between Bolt Holes Along Width:

1.250 inches 1st end

Bolt Hole Quantity:

4 1st end

Flange Length:

1.525 inches 1st end

End Application:

Hyd.Power unit, jered brown bros.Inc.

Flange Width:

3.030 inches 1st end

Connection Style:

Raised 1st end

Bolt Hole Diameter:

0.530 inches 1st end

Raised Face Height:

0.025 inches 1st end

Raised Face Diameter:

2.120 inches 1st end

End Flange Construction:

Solid 1st end

End Connection Design:

Elbow 1st end

End Fitting Component And Material:

Complete fitting steel all ends

Connection Type:

Raised face flange 1st end

Burst Test Pressure:

12000.0 pounds per square inch

First End Swivel Action Capability:

Not included

Layer Composition And Location:

Outer layer wrapped rubber, synthetic err-100

Maximum Operating Pressure:

3000.0 pounds per square inch

Hydrostatic Test Pressure:

6000.0 pounds per square inch

Flow Angle:

90.0 degrees 1st end

Outer Covering Environmental Protection:

Abrasion resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

72.000 inches

Flange Style:

Oval 1st end

Special Features:

Inner conveying tube material-rubber, synthetic

Media For Which Designed:

Hydraulic fluid single response

Specification Data:

Sae j517, 100r1, fc254 national std/spec

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0