Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-371-1326

Round

**Thread Class:** 

3b 1st end

# **Thread Direction:**

Right-hand 1st end

## Inside Diameter:

0.750 inches

#### **Tempurature Rating:**

-65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response

#### **Outside Diameter:**

1.075 inches

### Minimum Inside Bending Radius:

3.750 inches

#### Connection Style:

Swivel nut flare 1st end

# End Connection Design:

Straight 1st end

# End Fitting Component And Material:

Complete fitting aluminum alloy 6061 all ends

## **Connection Type:**

Threaded internal tube 1st end

## Second End Relationship With First End:

Identical

### **Burst Test Pressure:**

3600.0 pounds per square inch

### First End Swivel Action Capability:

Not included

### Layer Composition And Location:

Outer layer braided corrosion resistant steel wire err-100

### Maximum Operating Pressure:

200.0 pounds per square inch

#### **Thread Size:**

1.625 inches 1st end

#### Seat Angle:

37.0 degrees 1st end

## **Outer Covering Environmental Protection:**

Abrasion resistant

# Inside Surface Condition:

Convoluted

## Measuring Method And Length:

172.000 inches working

Nonmetallic Hose Assembly - Page 2 of 2



**Special Features:** 

Inner conveying tube material-plastic, polytetrafluoroethylene

**Thread Series Designator:** 

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A542a0